



## 6 in. Recessed Commercial LED Downlight, Selectable Color Temperature / Wattage, up to 1950 Lumens

MODEL: MRL-62200C

22  
WATTS  
ENERGY

1950  
LUMENS

5/5  
BRIGHTNESS



### PRODUCT SPECIFICATIONS

MODEL	MRL-62200C
MANUFACTURER	Maxxima
LIGHT TYPE	LED Downlight
DOWNLIGHT TYPE	Commercial
SHAPE	Round
QTY PACK SIZE	Single
WATTS	22
BRIGHTNESS	1950
CRI	90
LIFETIME HOURS	50000
DIMMABLE	Yes
ENERGY STAR RATED	Yes
ETL LISTED	Yes
IC RATED	Yes
SUITABLE FOR	Damp Locations
DEPTH	4.0"
DIAMETER	8.2"
WEIGHT	1.3 lbs
VOLTAGE	100-277V AC
WARRANTY	5 Years

### ADDITIONAL INFORMATION

<ul style="list-style-type: none"><li>• 3 CCT Select with switch (3000K/4000K/5000K)</li></ul>
<ul style="list-style-type: none"><li>• 3 Wattage Select - 10W 900 Lumens, 15W 1350 Lumens, 22W 1750 Lumens 3000K, 1950 Lumens 4000K/5000K</li></ul>
<ul style="list-style-type: none"><li>• Input Voltage: 100-277 VAC, 50/60 Hz</li></ul>
<ul style="list-style-type: none"><li>• Pre-Wired Whip (Flexible Metal Conduit) to Input Power &amp; Optional Dimming Control</li></ul>
<ul style="list-style-type: none"><li>• Wire Nuts &amp; Tension Spring Clips Included for Simple Installation</li></ul>
<ul style="list-style-type: none"><li>• Lamp Dimensions: 8.2" Diameter x 3.9" Depth</li></ul>
<ul style="list-style-type: none"><li>• Whip Length: 18.5"</li></ul>
<ul style="list-style-type: none"><li>• Safety Cable: 19.5"</li></ul>
<ul style="list-style-type: none"><li>• 0-10V Dimming</li></ul>
<ul style="list-style-type: none"><li>• Dimming Range 20% to 100%</li></ul>
<ul style="list-style-type: none"><li>• Operating Temperature: -20°C/ to 40°F</li></ul>
<ul style="list-style-type: none"><li>• Suitable for Damp Locations</li></ul>
<ul style="list-style-type: none"><li>• IC Rated</li></ul>