



3 in. 2700K Adjustable Slim Recessed LED Gimbal
Downlight, Canless IC Rated, 500 Lumens, Warm White
MODEL: MRL-S30700W

7
WATTS
ENERGY

40
WATTS
EQUIV

WARM
WHITE
2700K

500
LUMENS

3/5
BRIGHTNESS



PRODUCT SPECIFICATIONS

MODEL	MRL-S30700W
MANUFACTURER	Maxxima
LIGHT TYPE	LED Slim Downlight
DOWNLIGHT TYPE	Rotatable Gimbal
SHAPE	Round
QTY PACK SIZE	Single
WATTS	7
WATTS EQUIVALENT	40
BRIGHTNESS	500
LIGHT COLOR	Warm White
COLOR TEMPERATURE	2700K
CRI	80
LIFETIME HOURS	36000
DIMMABLE	Yes
BRIGHTNESS	3 of 5
IC RATED	Yes
SUITABLE FOR	Damp Locations
VOLTAGE	120V AC

WARRANTY	3 Years
----------	---------

ADDITIONAL INFORMATION

- Light Dimensions: 3.3" Dia. X 1.3" H
- J-Box Dimensions: 4.5" W x 1.4" H x 2.4" D
- Recommended Hole Cutout Diameter: 2.8"
- Includes Foam Gasket
- Barrel Connector from Light to J-Box. Blunt Cut Wires from J-Box
- 30° Gimbal Rotation Angle (15° Max Rotation Each Direction)
- 40° Beam Pattern
- Dimming Range: 10% to 100%
- Voltage: 120V AC
- Box LED Driver Rating: 28-42VDC
- Suitable for Damp Locations
- ETL Listed