



6 in. Slim Round Recessed LED Downlight, Canless IC Rated, 1050 Lumens, 5 CCT Color Selectable 2700K-5000K

MODEL: MRL-S61245

12 WATTS ENERGY **75**WATTS EQUIV

1050 LUMENS **5 CCT** 2700K, 3000K, 3500K 4000K, 5000K



PRODUCT SPECIFICATIONS

| MODEL | MRL-S61245 |
|------------------|----------------|
| MANUFACTURER | Maxxima |
| LIGHT TYPE | LED Downlight |
| DOWNLIGHT TYPE | Slim Panel |
| SHAPE | Round |
| QTY PACK SIZE | Single Pack |
| CASE PACK QTY | 24 |
| WATTS | 12 |
| WATTS EQUIVALENT | 75 |
| BRIGHTNESS | 1050 |
| CRI | 80 |
| LIFETIME HOURS | 50000 |
| DIMMABLE | Yes |
| ETL LISTED | Yes |
| IC RATED | Yes |
| SUITABLE FOR | Damp Locations |
| DEPTH | 0.9" |
| DIAMETER | 6.72" |

| WEIGHT | 0.85 lb |
|----------|---------|
| VOLTAGE | 120V AC |
| WARRANTY | 3 Years |
| COLOR | White |
| FINISH | Matte |

ADDITIONAL INFORMATION

| • 5 CCT | Select 2700K/3000K/3500K/4000K/5000K (switch on the side of J-Box) |
|------------|--|
| • Contro | ol up to 12 of these lights with a 150W max LED dimmer |
| No Cei | iling Can or Housing Required |
| • Power | Supply / Junction Box Included |
| • Recom | nmended Hole Cutout Diameter: 6.2" |
| • J-Box [| Dimensions: 1.4"H X 2.8"W X 4.75"D |
| • Cast A | sluminum Body |
| • Trim si | ize: 0.85" |
| • Dimmi | ing range: 20% - 100% |
| • Include | es foam gasket, air-tight rated |
| • 13.5" ir | nstallation cord from slim panel to J-Box |
| • Operat | ting temperature: -20°C to 40°C |