



## 4 in. Slim Recessed LED Downlight, Canless IC Rated, 750 Lumens, 5 CCT Color Selectable 2700K-5000K

MODEL: **MRL-S40905**

**10**

WATTS ENERGY

**60**

WATTS EQUIV

**750**

LUMENS

**5 CCT**

2700K, 3000K, 3500K  
4000K, 5000K



### PRODUCT SPECIFICATIONS

MODEL	MRL-S40905
MANUFACTURER	Maxxima
LIGHT TYPE	LED Downlight
DOWNLIGHT TYPE	Slim Panel
SHAPE	Round
QTY PACK SIZE	Single Pack
CASE PACK QTY	24
WATTS	10
WATTS EQUIVALENT	60
BRIGHTNESS	750
CRI	80
LIFETIME HOURS	50000
DIMMABLE	Yes
ETL LISTED	Yes
IC RATED	Yes
SUITABLE FOR	Damp Locations
DEPTH	0.9"
DIAMETER	4.75"

WEIGHT	0.66 lb
VOLTAGE	120V AC
WARRANTY	3 Years
COLOR	White
FINISH	Matte

### ADDITIONAL INFORMATION

- 5 CCT Select 2700K/3000K/3500K/4000K/5000K (switch on the side of J-Box)
- Control up to 16 of these lights with a 150W max LED dimmer
- No Ceiling Can or Housing Required
- Power Supply / Junction Box Included
- Recommended Hole Cutout Diameter: 4.25"
- J-Box Dimensions: 1.4"H X 2.8"W X 4.75"D
- Cast Aluminum Body
- Trim size: 0.75"
- Dimming range: 20% - 100%
- Includes foam gasket, air-tight rated
- Cast aluminum body
- 13.5" installation cord from slim panel to J-Box
- Operating temperature: -20°C to 40°C