



4 in. Slim Square Recessed LED Downlight, Canless IC
Rated, 750 Lumens, 5 CCT Color Selectable 2700K-
5000K

MODEL: MRL-S40905S

10

WATTS ENERGY

60

WATTS EQUIV

750

LUMENS

5 CCT

2700K, 3000K, 3500K
4000K, 5000K



DIMMABLE

PRODUCT SPECIFICATIONS

MODEL	MRL-S40905S
MANUFACTURER	Maxxima
LIGHT TYPE	LED Slim Downlight
DOWNLIGHT TYPE	Slim Panel
SHAPE	Round
QTY PACK SIZE	Single Pack
WATTS	10
WATTS EQUIVALENT	60
BRIGHTNESS	750
CRI	82
LIFETIME HOURS	50,000
DIMMABLE	Yes
ETL LISTED	Yes
SUITABLE FOR	Damp Locations
DEPTH	1"
DIAMETER	4.7"
WEIGHT	.7 lbs
VOLTAGE	120V AC

WARRANTY	3 Years
COLOR	White
FINISH	Matte

ADDITIONAL INFORMATION

- 5 CCT Select 2700K/3000K/3500K/4000K/5000K (switch on the side of J-Box)
- Control up to 12 of these lights with a 150W max LED dimmer
- No Ceiling Can or Housing Required
- Fully integrated LED downlight
- Power Supply / Junction Box Included
- Recommended Hole Cutout Diameter: 4.2" x 4.2"
- J-Box Dimensions: 1.37"H X 2.7"W X 4.11"D
- Cast Aluminum Body
- Trim size: 0.9"
- Dimming range: 20% - 100%
- Includes foam gasket, air-tight rated
- Cast aluminum body
- 13.5" installation cord from slim panel to J-Box
- Operating temperature: -4°F to 140°F