



4 in. Slim Square Recessed LED Downlight, Canless IC Rated, 750 Lumens, 5 CCT 2700K-5000K (12 Pack) MODEL: MRL-S40905S-12

10
WATTS ENERGY

60
WATTS EQUIV

750
LUMENS

5 CCT
2700K, 3000K, 3500K
4000K, 5000K



PRODUCT SPECIFICATIONS

| | |
|------------------|--------------------|
| MODEL | MRL-S40905S-12 |
| MANUFACTURER | Maxxima |
| LIGHT TYPE | LED Slim Downlight |
| DOWNLIGHT TYPE | Slim Panel |
| SHAPE | Round |
| QTY PACK SIZE | 12 Pack |
| WATTS | 10 |
| WATTS EQUIVALENT | 60 |
| BRIGHTNESS | 750 |
| CRI | 82 |
| DIMMABLE | Yes |
| ETL LISTED | Yes |
| SUITABLE FOR | Damp Locations |
| DEPTH | 1" |
| DIAMETER | 4.75" |
| WEIGHT | .7 lbs |
| VOLTAGE | 120V AC |
| WARRANTY | 3 Years |

| | |
|--------|-------|
| COLOR | White |
| FINISH | Matte |

ADDITIONAL INFORMATION

- 5 CCT Select 2700K/3000K/3500K/4000K/5000K (switch on the side of J-Box)
- Control up to 12 of these lights with a 150W max LED dimmer
- No Ceiling Can or Housing Required
- Power Supply / Junction Box Included
- Recommended Hole Cutout Diameter: 4.2" x 4.2"
- J-Box Dimensions: 1.37"H X 2.7"W X 4.11"D
- Cast Aluminum Body
- Trim size: 0.9"
- Dimming range: 20% - 100%
- Includes foam gasket, air-tight rated
- Cast aluminum body
- 13.5" installation cord from slim panel to J-Box
- Operating temperature: -4°F to 140°F