



## 10 in. Recessed Commercial LED Downlight, Selectable Color Temperature / Wattage, up to 3000 Lumens

MODEL: MRL-104005C

40 WATTS ENERGY

3000 LUMENS





## PRODUCT SPECIFICATIONS

| MODEL          | MRL-104005C    |
|----------------|----------------|
| MANUFACTURER   | Maxxima        |
| LIGHT TYPE     | LED Downlight  |
| DOWNLIGHT TYPE | Commercial     |
| SHAPE          | Round          |
| QTY PACK SIZE  | Single Pack    |
| WATTS          | 40             |
| BRIGHTNESS     | 3000           |
| CRI            | 90             |
| LIFETIME HOURS | 50,000         |
| DIMMABLE       | Yes            |
| UL LISTED      | Yes            |
| IC RATED       | Yes            |
| SUITABLE FOR   | Damp Locations |
| DEPTH          | 5"             |
| DIAMETER       | 11.6"          |
| WEIGHT         | 2.3 lbs        |
| VOLTAGE        | 100-277V AC    |

| WARRANTY | 5 Years |
|----------|---------|
| FINISH   | Glossy  |

## ADDITIONAL INFORMATION

| 5 CCT Select with switch (2700K/3000K/3500K/4000K/5000K     3 Wattage Select - 20W 1700 Lumens, 30W 2300 Lumens, 40W 3000 Lumens     Input Voltage: 100-277 VAC, 50/60 Hz     Pre-Wired Whip (Flexible Metal Conduit) to Input Power & Optional Dimming |
|---|
| <ul> <li>Input Voltage: 100-277 VAC, 50/60 Hz</li> <li>Pre-Wired Whip (Flexible Metal Conduit) to Input Power &amp; Optional Dimming</li> </ul>   |
| Pre-Wired Whip (Flexible Metal Conduit) to Input Power & Optional Dimming   |
|   |
| Control   |
| Wire Nuts & Tension Spring Clips Included for Simple Installation   |
| • Lamp Dimensions: 11.62" Diameter x 5" Depth - Trim Width 2.5"   |
| • Whip Length: 27"  |
| Safety Cable: 19.5"   |
| 0-10V Dimming   |
| • Dimming range 20%-100%  |
| • Operating temperature: -4°F - 104°F   |
| Suitable for Damp Locations   |
| IC Rated  |
| CRI Rating 90   |