



2 in. Slim Round Recessed Anti-Glare LED Downlight, White Trim, Canless IC Rated, 600 Lumens, 5 CCT 2700K-5000K

MODEL: MRL-S20803

9 WATTS ENERGY 35 WATTS EQUIV 600 LUMENS **5 CCT** 2700K, 3000K, 3500K 4000K, 5000K



PRODUCT SPECIFICATIONS

| MODEL | MRL-S20803 |
|------------------|--------------------|
| MANUFACTURER | Maxxima |
| LIGHT TYPE | LED Slim Downlight |
| DOWNLIGHT TYPE | Slim Panel |
| SHAPE | Round |
| QTY PACK SIZE | Single Pack |
| WATTS | 9 |
| WATTS EQUIVALENT | 35 |
| BRIGHTNESS | 600 |
| CRI | 90 |
| LIFETIME HOURS | 50000 |
| DIMMABLE | Yes |
| ETL LISTED | Yes |
| SUITABLE FOR | Damp Locations |
| DEPTH | 2.58" |
| DIAMETER | 3.14" |
| WEIGHT | .79 |
| VOLTAGE | 120V AC |
| WARRANTY | 3 Years |
| COLOR | White |
| FINISH | Matte |

ADDITIONAL INFORMATION

| • 5 CCT Select 2700K/3000K/3500K/4000K/5000K (switch on the side of J-Box) |
|--|
| High CRI rating (90) provides the most accurate appearance of colors in the room |
| No ceiling can or housing required |
| Power Supply / Junction Box included |
| Recommended hole cutout diameter: 2.5" |
| • J-Box Dimensions: 5.2" W x 1.62" H x 1.17" D |
| • Trim size: 0.83" |
| Cast aluminum Body |
| Beam angle: 36° |
| • Dimming range: 20% - 100% |
| Includes foam gasket, air-tight rated |
| 9.3" installation cord from downlight to J-Box |
| Operating temperature: -4°F to 104°F |