



## 4 in. 2 Head Trimless LED Slim Square Recessed Anti-Glare Gimbal Downlight, White, Canless IC Rated, 2000 Lumens, 5 CCT 2700K-5000K


MODEL: **MRL-S430052**

**30**  
WATTS ENERGY

**150**  
WATTS EQUIV

**2000**  
LUMENS

**5 CCT**  
2700K, 3000K, 3500K  
4000K, 5000K



### PRODUCT SPECIFICATIONS

MODEL	MRL-S430052
MANUFACTURER	Maxxima
LIGHT TYPE	LED Slim Downlight
DOWNLIGHT TYPE	Trimless
QTY PACK SIZE	Single Pack
CASE PACK QTY	8
WATTS	30
WATTS EQUIVALENT	150
BRIGHTNESS	2000
CRI	90
LIFETIME HOURS	50,000
DIMMABLE	Yes
BEAM SPREAD	40°
ETL LISTED	Yes
IC RATED	Yes
SUITABLE FOR	Wet Locations
WIDTH	4"
LENGTH	7.5"
DEPTH	3.5"
WEIGHT	3.4 lbs
VOLTAGE	120V AC
WARRANTY	3 Years
COLOR	White
FINISH	Matte

### ADDITIONAL INFORMATION

- 5 CCT Select 2700K/3000K/3500K/4000K/5000K (switch on back of fixture)
- No ceiling can or housing required
- Power Supply / Junction Box included
- Recommended hole cutout diameter: 7 3/4" x 4"
- Two adjustable eyeballs: 15° in any direction
- Beam Spread 40°
- Integrated LED clicks into place and is removable with provided tool
- Frameless spackle area: 1.25"
- Cast aluminum Body
- Dimming range: 10% - 100%
- 14" wire length to j-box
- Operating temperature: -4°F to 104°F