

4 in. 3 Head Trimless LED Slim Square Recessed Anti-Glare Gimbal Downlight, White, Canless IC Rated, 3000 Lumens, 5 CCT 2700K-5000K

MODEL: **MRL-S445053**



45

WATTS ENERGY

225


WATTS EQUIV

3000

LUMENS

5 CCT

2700K, 3000K, 3500K
4000K, 5000K



PRODUCT SPECIFICATIONS

MODEL	MRL-S445053
MANUFACTURER	Maxxima
LIGHT TYPE	LED Slim Downlight
DOWNLIGHT TYPE	Trimless
QTY PACK SIZE	Single Pack
CASE PACK QTY	4
WATTS	45
WATTS EQUIVALENT	225
BRIGHTNESS	3000
CRI	90
LIFETIME HOURS	50,000
DIMMABLE	Yes
BEAM SPREAD	40°
ETL LISTED	Yes
IC RATED	Yes
SUITABLE FOR	Wet Locations
WIDTH	4"
LENGTH	11.5"
DEPTH	3.5"
WEIGHT	4.7 lbs
VOLTAGE	120V AC
WARRANTY	3 Years
COLOR	White
FINISH	Matte

ADDITIONAL INFORMATION

- 5 CCT Select 2700K/3000K/3500K/4000K/5000K (switch on back of fixture)
- No ceiling can or housing required
- Power Supply / Junction Box included
- Recommended hole cutout diameter: 11 5/8" x 4"
- Three adjustable eyeballs: 15° in any direction
- Beam Spread 40°
- Integrated LED clicks into place and is removable with provided tool
- Frameless spackle area: 1.25"
- Cast aluminum Body
- Dimming range: 10% - 100%
- 14" wire length to j-box
- Operating temperature: -4°F to 104°F