



4 in. Slim Square Recessed Anti-Glare LED Downlight,
White Trim Black Baffle, Canless IC Rated, 1200 Lumens,
5 CCT 2700K-5000K

MODEL: **MRL-S41503SBW**

15

WATTS ENERGY

90

WATTS EQUIV

1200

LUMENS

5 CCT

2700K, 3000K, 3500K
4000K, 5000K



DIMMABLE

PRODUCT SPECIFICATIONS

| | |
|------------------|--------------------|
| MODEL | MRL-S41503SBW |
| MANUFACTURER | Maxxima |
| LIGHT TYPE | LED Slim Downlight |
| DOWNLIGHT TYPE | Anti-Glare |
| SHAPE | Square |
| QTY PACK SIZE | Single Pack |
| CASE PACK QTY | 20 |
| WATTS | 15 |
| WATTS EQUIVALENT | 90 |
| BRIGHTNESS | 1200 |
| CRI | 90 |
| LIFETIME HOURS | 50,000 |
| DIMMABLE | Yes |
| ETL LISTED | Yes |
| IC RATED | Yes |
| SUITABLE FOR | Damp Locations |
| WIDTH | 4.8" |
| LENGTH | 4.8" |

| | |
|----------|-------------|
| DEPTH | 2.5" |
| WEIGHT | 1.1 lb |
| VOLTAGE | 120V AC |
| WARRANTY | 3 Years |
| COLOR | White/Black |

ADDITIONAL INFORMATION

- 5 CCT Select 2700K/3000K/3500K/4000K/5000K (switch inside J-Box)
- No ceiling can or housing required
- Power Supply / Junction Box included
- Recommended Hole Cutout Diameter: 4"
- J-Box Dimensions: 1.25" H X 3.4" W X 3.4" D
- Trim size: 1"
- Cast aluminum body
- Dimming range: 20% - 100%
- Includes foam gasket, air-tight rated
- 9" installation cord
- Beam angle: 36°